

*Optional blocker precisely control the cleave length for mechanical splice.*



**INNO INSTRUMENT, Inc.**  
65-3, Sangdaewondong, Jungwongu,  
Sungnamsi, Kyeonggido,  
Korea 462-807  
Tel: +82 31 742 8755  
Fax: +82 31 742 8799  
Email: info@innoinstrument.com  
www.innoinstrument.com

- \* Optional Blocker cooperates with the first slot-- 24mm cleave length.
- \* Optional Blocker cooperates with the second slot-- 22mm cleave length.
- \* Optional Blocker cooperates with the third slot-- 19.5mm cleave length.
- \* Optional Blocker cooperates with the fourth slot-- 18mm cleave length.

\* Design is subject to change without any prior notice for the improvement.  
\* Picture for reference only. Please take In-kind as standard.



INNO INSTRUMENT, Inc.

**DC300** Indoor Cable Stripper

**Strip the Jacket:**



**1** Insert the cable into the central tunnel as shown in picture.



**2** Compress the stripper, and then pull the cable to strip the jacket of indoor cable.




**3** Compress the stripper, and then pull the cable to strip the coating of indoor cable.



**4** Move the cable to the scale on the ruler that indicate the length you need.

**Strip the Coating:**



**1** Insert the cable into the side path until the cutting surface of jacket touch the end of the locating slot.

**Blade Adjustment:**

Adjust the tightening screw to achieve the best stripping effect.

